



Stone Works

Floor tile, Wall tile
—{5 colours}

What modern day minimalist demands,
with a range of neutral colours giving you
the freedom to achieve the perfect balance
in colour and taste.

Stone Works Collection

What modern day minimalist demands, with a range of neutral colours giving you the freedom to achieve the perfect balance in colour and taste.



Type	Sizes	Avaiable in
Glazed Porcelain Tile	30×60 (12”x24”) 60×60 (24”x24”)	• Matt

Description

									
Digital Print	Glazed Porcelain	Rectified Tile	Normal Body	Slight Variation	Suitable Outdoor	Frost Resistant	Abrasion Resistance	C.O.F. (Wet)	C.O.F. (Dry)



-Stone WHITE-



-Stone CREAM-



-Stone SILVER-




-Stone GREY-




-Stone CARBON-

Decor




M1
30X30
(12”X12”)



M2
30X30
(12”X12”)



M3
30X30
(12”X12”)



Skirting
10x30 (4”x12”)
10x60 (4”x24”)

Special Pieces

Stone Works

Size	PCS/BOX	M2/BOX	Boxes/Pallet	KG/Pallet	M2/Pallet
30X60 (12”X24”)	8	1,44	40	1.280,00	57,60
60X60 (24”X24”)	4	1,44	36	1.152,00	51,84
45x90 (18”X36”)	3	1,22	56	1.568,00	68,32
MOSAIC1 5X5 (2”X2”)	11	0,99	48	1.220,00	
MOSAIC2 5X10 (2”X4”)	11	0,99	48	1.220,00	
MOSAIC3 FINGER	11	0,99	48		
BN 10X30 (4”X12”)	16				
BN 10X60 (4”X24”)	12				

* The packing information is only a guide and can sometimes vary from the real packing

CARACTERÍSTICAS TÉCNICAS Technical characteristics		NORMA DE ENSAYO TEST ESTANDAR UNE-ISO-10545	NORMA DE PRODUCTO PRODUCT STANDARD ISO 13006	VALORES PROMEDIA THE TILE COMPANY THE TILE COMPANY AVERAGE VALUES
	LONGITUD Y ANCHURA Length and width	10545-2	± 0.6%	± 0.1%
	GROSOR Thickness		± 5.0%	± 5.0%
	RECTITUD DE LOS LADOS Straightness of sides		± 0.5%	± 0.1%
	ORTOGONALIDAD Rectangularity		± 0.6%	± 0.1%
	PLANITUD DE LA SUPERFICIE Surface planarity		± 0.5%	±0.25%
	ABSORCIÓN DE AGUA Water absorption	UNE-EN-ISO 10545-3	≤ 0.5%	≤ 0.1%
	RESISTENCIA A LA FLEXIÓN Bending strength	UNE-EN-ISO 10545-4	MIN 35 N/MM2	52 N/MM2
	CARGA DE ROTURA Breakage load	UNE-EN-ISO 10545-4	MIN 1300 N	2000 N
	RESISTENCIA A LA ABRASIÓN PROFUNDA Deep abrasion resistance	UNE-EN-ISO 10545-6	MAX 175 MM3	120 MM3
	DILATACIÓN TÉRMICA Thermal expansion	UNE-EN-ISO 10545-8	METODO ENSAYO DISPONIBLE Test method available	
	RESISTENCIA AL HIELO Frost resistance	UNE-EN-ISO 10545-12	RESISTE Resistant	RESISTE Resistant
	RESISTENCIA A ATAQUES QUÍMICOS Resistance to chemical attack	UNE-EN-ISO 10545-13	RESISTE Resistant	RESISTE Resistant
	RESISTENCIA A LAS MANCHAS Resistance to staining	UNE-EN-ISO 10545-14	CONFORME A LAS NORMAS Complies with standards	CONFORME A LAS NORMAS Complies with standards

MANCHAS STAINS	PRODUCTOS QUÍMICOS CHEMICALS	DETERGENTE DETERGENT CLEANER
FRUTAS, TOMATE SALSA, CHOCOLATE Fruits, tomato, sauces, chocolate	AMONIACO, ÁCIDO CLORHÍDRICO Ammonia, hydrochloric acid	DETERGENTE ALCALINO Alkaline cleaner/Detergent
ACEITE VEGETAL/ANIMAL, VINO, CERVEZA, HELADOS, CAFÉ Vegetable oil, wine, beer, ice creams, coffee	ÁCIDO CLORHÍDRICO 10% AMONIACO Hydrochloric acid 10% ammonia	DETERGENTE ALCALINO Alkaline cleaner/Detergent
SANGRE Blood	HIPOCLORITO SÓDICO Sodium hypochloride	DETERGENTE ALCALINO Alkaline cleaner/Detergent
RESTOS DE CEMENTO Cement residue	ÁCIDO CLORHÍDRICO 10% Hydrochloric acid 10%	DETERGENTE ÁCIDO Acid detergent
ÓXIDO Y RESTOS METÁLICOS Oxide and metallic residue	ÁCIDO CLORHÍDRICO, ÁCIDO SULFÚRICO Hydrochloric acid, sulphuric acid	DETERGENTE ÁCIDO Acid detergent
NICOTINA Nicotine	ÁCIDO CÍTRICO Citric acid	DETERGENTE ALCALINO Alkaline cleaner/Detergent
GOMA DE ZAPATO, NEUMÁTICO Shoe or tire marks	TRICLORO ETILENO, ACETONA Acetone	DISOLVENTE ORGÁNICO Organic solvent
ACEITES LUBRICANTES, LÁPIZ, BETÚN Lubricant oil, pencil lead, grease	TRICLORO ETILENO, ACETONA Acetone	DISOLVENTE ORGÁNICO Organic solvent
RESINAS, LACA DE ESMALTE Resin, nail varnish	DISOLVENTE NÍTRICO Nitric solvent	DISOLVENTE ORGÁNICO Organic solvent
TINTAS Ink	SOLUCIÓN DE HIPOCLORITO SÓDICO O ÁCIDO SULFÚRICO, ÁCIDO NÍTRICO Sodium hydrochloride solution, sulphuric acid, nitric acid	DETERGENTE ÁCIDO Acid detergent

the **tile**_company